

**CHCNAV**

**P5**

**GEODETTIC GNSS  
REFERENCE STATION**



**NAVIGATION &  
INFRASTRUCTURE**

# SMART GNSS GEODETTIC REFERENCE STATION

The P5 GNSS reference station integrates 624 channels for tracking multi-constellation GNSS signals, large storage and battery capacity, secure and diverse network connectivity, and smart access rights management and makes it extremely reliable and easy to use. The P5 GNSS receiver is shock resistant and suits any environment, and it features voltage stabilization, lightning protection, real-time self-diagnosis, and status monitoring to ensure uninterrupted operation. The P5 is an advanced GNSS reference station to provide positioning services in various demanding industries, such as GNSS ground augmentation, deformation monitoring, atmospheric research, seismic research, precision agriculture, machine control, and vehicle and ship navigation.

## 624-CHANNEL ADVANCED GNSS TRACKING

### Full constellation for superior GNSS raw data

The 624-channel P5 GNSS simultaneously tracks signals from GPS, GLONASS, Galileo, BeiDou, and SBAS satellites with outstanding GNSS raw data quality. The integration of the P5 GNSS reference stations as the foundation of RTK networks guarantees optimal GNSS RTK corrections resulting in the highest quality GNSS rover positioning.

## SMART DATA MANAGEMENT

### Large data storage and advanced web access

With 32GB of internal storage and up to 1TB of external storage, the P5 can simultaneously record up to 8 separate data sessions, providing data storage in the standard Rinex 3.02 format for up to 7 years. In addition, its embedded FTP server or FTP push to a remote site ensures data integrity and ease of use.

## MULTIPLE POWER SOURCES

### Reliable and uninterrupted operation

The P5 supports both DC and AC external power inputs to ensure a stable and continuous electrical supply. The built-in high-capacity 17,000 mAh battery provides up to 20 hours of non-stop backup operation in the event of an external power outage. The P5's electronic design results in an MTBF (mean time between failures) of over 35,000 hours.

## VERSATILE NETWORK CONNECTION MODES

### Robust and secure GNSS data streaming

The P5 supports remote connections via Intranet, Ethernet, 4G and Wi-Fi for easy access, configuration and data transfer. The redundant network connectivity feature allows the P5 to automatically switch between Ethernet and 4G wireless network connections, ensuring stable and reliable GNSS data streaming. The P5 also supports OpenVPN intranet penetration and multiple protocol stacks to easily create HTTP/HTTPS web access without static IP. In addition, the P5 has several security layers, such as multiple user permissions, web interface restrictions, HTTPS encryption to prevent unauthorized access and built-in firewall, port and MAC filtering.

## FLAWLESS GNSS DATA INTEGRITY

### Industrial design for optimal data integrity

The P5 GNSS is IP67-rated water and dust resistant to withstand challenging environmental conditions at its installation site, reducing potential downtime due to moisture or dust ingress. Its integrated design and advanced power supply ensure uninterrupted operation 24 hours a day, 7 days a week. The P5 provides continuous status information on its control screen and allows remote monitoring of power supply conditions, network status, firmware version, etc. Email alerts and automatic reconnection protocols can be enabled through the receiver's self-diagnosis and status monitoring.



## GNSS GEODETIC REFERENCE STATION



### OPTIMAL FOR GNSS NETWORKS

Supported by CPS to manage GNSS RTK networks

CPS (CHCNAV Precision Service) is the third generation of advanced distributed software solutions for GNSS RTK networks developed by CHC Navigation. CPS is compatible with the latest QZSS and BDS III navigation systems and fulfills the requirements of regional and national CORS and GNSS RTK networks. When associated with the P5 GNSS reference station, CPS uses the most advanced and proprietary CHCNAV VNS algorithm to establish error resolution models for the ionospheric delay, tropospheric delay, orbital error, multipath effect, etc., for the complete network. In addition, it features optimized spatial error corrections for each end user using an enhanced virtual reference station to ensure a reliable RTK fixed rate and positioning accuracy. The CPS quality control module also monitors P5 GNSS operation, network status, and data quality in the real time.



# SPECIFICATIONS

GNSS characteristics	
Channels	624
GPS	L1, L2, L5
GLONASS	L1, L2
Galileo	E1, E5a, E5b
BeiDou	B1, B2, B3, B1c, B2a
QZSS	L1, L5
SBAS <sup>(1)</sup>	L1

GNSS accuracies <sup>(2)</sup>	
Real time kinematic (RTK)	Horizontal: 8 mm + 1 ppm RMS Vertical: 15 mm + 1 ppm RMS Initialization time: < 8 s Initialization reliability: > 99.9%
Post-processing static	Horizontal: 2.5 mm + 0.5 ppm RMS Vertical: 5 mm + 0.5 ppm RMS
Post-processing static (long observation)	Horizontal: 3 mm + 0.1 ppm RMS Vertical: 3.5 mm + 0.4 ppm RMS

Hardware	
Size (L x W x H)	200 mm x 150 mm x 69 mm (7.9 in x 5.9 in x 2.7 in)
Weight	2.15 kg (75.8 oz) with battery
Environment	Operating: -40°C to +65 °C (-40°F to +149°F) Storage: -45°C to +80°C (-49°F to +176°F)
Humidity	100%
Ingress protection	IP67 waterproof and dustproof, protected from temporary immersion to depth of 1 m
Shock	IEC68-2-27


Electrical	
Power consumption	5 W (depending on user settings)
Internal battery capacity	17,000 mAh, 7.4 V
Operating time on internal battery <sup>(3)</sup>	Up to 20 h (depending receiver configuration)
External power	9 V DC to 36 V DC

Certifications and Calibrations	
FCC Part 15 (class B Device), FCC Part 22, 24, 90; CE Mark; Method 514.7, IGS	

Communications and Data storage	
Ports	1 x 10-pin LEMO port (external power, RS-232) 1 x USB 2.0 port (data download, firmware update) 1 x LAN port HTTP / HTTPs, TCP/IP, UDP, FTP, NTRIP Caster, NTRIP Server, NTRIP Client – Simultaneously transmits multiple data stream – Support proxy server and route table 1 x DB9 port 1 x GNSS antenna port 1 x SIM card slot
Protocols	Correction formats: RTCM2.x, RTCM 3.x Observables: HCN, HRC, RINEX2.x, RINEX3.x Position/Status I/O: NMEA 0183 output Met sensor
Internal data logging and position	Output frequency up to 20 Hz (optional) Storage capacity 32 GB
External storage	Up to 1 TB
Bluetooth <sup>®</sup>	V 4.1
Wi-Fi	802.11 b/g/n, access point mode
Network modem (Internal 4G modem)	TE (FDD): B1, B3, B8, all bands with diversity LTE (TDD): B38, B39, B40, B41, all bands with diversity DS-HSPA+/HSPA+/HSPA/UMTS: B1, B5, B8, B9, all bands with diversity TD-SCDMA: B34, B39 EDGE/GPRS/GSM 900/1800 MHz

\*All specifications are subject to change without notice.

(1) SBAS will be provided through future firmware upgrade. (2) Accuracy and reliability are determined under open sky, free of multipaths, optimal GNSS geometry and atmospheric condition. Performances assume minimum of 5 satellites, follow up of recommended general GPS practices. (3) Battery life is subject to operating temperature.



© 2022 Shanghai Huace Navigation Technology Ltd. All rights reserved. The CHC and CHC logo are trademarks of Shanghai Huace Navigation Technology Limited. All other trademarks are the property of their respective owners. Revision May 2022.

WWW.CHCNAV.COM | SALES@CHCNAV.COM

CHC Navigation Headquarter  
Shanghai Huace Navigation Technology Ltd.  
599 Gaojing Road, Building D,  
Shanghai, 201702, China  
+86 21 54260273

CHC Navigation Europe  
Infopark Building, Sétány 1, 1117  
Budapest, Hungary  
+36 20 235 8248 +36 20 5999 369  
info@chcnav.eu

CHC Navigation USA LLC  
6380 S. Valley View Blvd Suite 246  
Las Vegas, NV 89118 USA  
+1 480 399 9533

CHC Navigation India  
409 Trade Center, Khokhra Circle,  
Maninagar East, Ahmedabad,  
Gujarat, India  
+91 90 99 98 08 02